


12"-60" DUAL WALL HP STORM WATERTIGHT CONNECTION USING A MANHOLE BOOT (CORED HOLE OR PRE-CAST) W/ CORRUGATED PIPE ADAPTER GASKET



PIPE SIZE	PIPE OD	PRESS SEAL® SYSTEMS			KOR-N-SEAL®		
		CORRUGATED PPE ADAPTER GASKET	PSX: DIRECT DRIVE *	CAST-A-SEAL *	CORRUGATED PPE ADAPTER GASKET *	KOR-N-SEAL® *	
						SERIES I OR II	SERIES 306
12" (300mm)	14.5" (368.3mm)	1250PS	18Y	CAS 802	CGA-12A	S106-20BWS	N/A
15" (375mm)	17.6" (447.0mm)	1550PS	22L	CAS 802	CGA-15A	S106-20WS	S306-22
18" (450mm)	21.2" (538.5mm)	1850PS	24A	CAS 802	CGA-18A	S206-24L	S306-24L
24" (600mm)	28.1" (713.7mm)	2450PS	32L	CAS 802	CGA-24A	S206-32	S306-32
30" (750mm)	35.3" (896.6mm)	3050PS	40L	CAS 802	CGA-30A**	S206-38L	S306-38LS-PG
36" (900mm)	41.1" (1043.9mm)	N/A	N/A	CAS 802	CGA-36A**	S206-44L	S306-44LS-PG
42" (1050mm)	47.2" (1198.9mm)	N/A	N/A	CAS 802	CGA-42A**	S206-52L	S306-52L
48" (1200mm)	53.8" (1366.5mm)	N/A	N/A	CAS 802	CGA-48A**	S206-58L	S306-58L
54" (1350mm)	N/A	N/A	N/A	CAS 802	N/A	N/A	N/A
60" (1500mm)	66.5" (1689.1mm)	N/A	N/A	CAS 802	CGA-60A**	S206-70L	N/A

NOTES:
 PERFORMANCE HIGHLY DEPENDENT ON INSTALLATION. CONTRACTOR MUST ENSURE MANHOLE GASKET IS UNIFORMLY SEATED AROUND STRUCTURE ADAPTER. EXTRA PRECAUTIONS MUST BE TAKEN TO PREVENT DIFFERENTIAL SETTLEMENT BETWEEN THE PIPE AND MANHOLE.

SEE STANDARD DETAIL STD-201 AND TECHNICAL NOTE: 5.04 CONNECTIONS TO MANHOLES AND STRUCTURES FOR INSTALLATION RECOMMENDATIONS.

* THIRD PARTY - CODES AS SUPPLIED BY MANUFACTURER
 ** NOT RATED FOR WATERTIGHT FIELD TESTING
 KOR-N-SEAL is a registered trademark of NPC, Inc. (www.npc.com)
 CAST-A-SEAL is a registered trademark of PRESS-SEAL GASKET CORPORATION. (www.press-seal.com)
 PSX Systems are a product of PRESS-SEAL GASKET CORPORATION. (www.press-seal.com)
 © 2016 ADS, INC.

5	ADDED METRIC UNITS AND RENAMED	TJR	02/01/16	
REV.	DESCRIPTION	BY	MM/DD/YY	CHK'D

ADVANCED DRAINAGE SYSTEMS, INC. ("ADS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO ADS. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. ADS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

**12"-60" HP STORM MH
 BOOT AND CORR ADAPTER GASKET**
 DRAWING NUMBER: STD-207B

ADS
 ADVANCED DRAINAGE SYSTEMS, INC.
 4640 TRUEMAN BLVD
 HILLIARD, OHIO 43026

DRAWN BY	JAB
DATE	4/3/09
CHK'D BY	
SCALE	NTS
SHEET	1 OF 1