

## NOTES

- 1. EXCAVATE AND LEVEL INSTALLATION AREAS
- SMOOTH IRREGULARITIES IN THE EXCAVATION. A LEVEL FLAT SURFACE IS REQUIRED.
- INSTALL ARC LEACHING CHAMBERS IN ADJACENT ROWS TO COVER DESIRED AREA.
- INSTALL UNIVERSAL END CAP AND SECURE IN PLACE WITH BACKFILL.
- 5. INSTALL 4" PIPE TO EACH ROW OF ARC CHAMBER USING KNOCKOUTS PROVIDED IN THE UNIVERSAL END CAPS.

- ENDS OF ROWS MAY BE CONNECTED WITH PIPING TO IMPROVE DISTRIBUTION.
- FILL PERIMETER AND INTERIOR SIDEWALL AREAS TO TOP OF CHAMBERS AND WALK INTO PLACE. AVOID LARGE ROCKS OR DEBRIS IN COVER MATERIAL.
- COVER ARC LEACHING CHAMBERS TO A MINIMUM OF 12" OF GRANULAR COVER AFTER CONSOLIDATION FOR H-10 APPLICATIONS. AVOID LARGE ROCKS OR DEBRIS IN COVER MATERIAL. COVER HEIGHTS AND LIVE LOADING LIMITS ARE IMPACTED BY BOTH SOIL TYPE AND COMPACTION REQUIREMENTS. CONTACT ADS WHEN POOR SOILS ARE ENCOUNTERED AND FOR MAXIMUM FILL HEIGHTS. LIVE LOAD CONDITIONS ARE NOT RECOMMENDED.

ADVANCED DRAINAGE SYSTEMS, INC. ("AOS") HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO AOS. THIS DRAINING IS INFERNICES FOR THIS DEPOIT THE COMPONENTS AS REQUESTED. AOS HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS ADS INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HERRIN AEE GENERAL RECOMMENDATIONS AND AEE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PROPORT OF CONSTRUCTION. IT IS THE DESIGN ENGINEER RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HERRIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS OF THIS PROVIDED HERRIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS.

CLUSTER SYSTEM INSTALLATION

DRAWING NUMBER: STD-907CD



| TJR | Mrs | 09/05/07 | CKS | Cou.a. | NTS | NTS | OF | OF |