



ADS GEOSYNTHETICS 00S1TT EROSION CONTROL BLANKET

Scope

This specification describes ADS Geosynthetics 00S1TT erosion control blanket.

Erosion Control Blanket Requirements

ADS Geosynthetics 00S1TT temporary erosion control blanket is composed of a 100% certified weed free agricultural straw matrix mechanically (stitch) bonded on two inch centers to a single synthetic, photodegradable net. The net is secured to the top of the RECP to restrain the straw matrix once installed. ADS Geosynthetics 00S1TT blanket is intended for use in channels or on slopes requiring erosion protection for a period up to twelve months. Actual field longevity is dependent on soil and climatic conditions.

Each roll of ADS Geosynthetics 00S1TT is manufactured under a quality assurance program to ensure a continuous distribution of fibers and consistent thickness. Verified values are provided in Table 1 and product characteristics are provided in Tables 2 and 3. Values provided in Tables 1, 2 and 3 represent expected values at the time of manufacture. Installation instructions and performance data are available from ADS Geosynthetics Technical Support Division. ADS Geosynthetics 00S1TT conforms to the physical property values listed below:

Erosion Control Blanket Properties

Table 1 - Verified Values			
Tested Property	Test Method	Value	Units
Tensile Strength	ASTM D6818	4.8 (MD), 4.8 (TD)	lb/in
Elongation	ASTM D6818	15 (MD), 20 (TD)	%
Mass per Unit Area	ASTM D6475	8.0	oz/yd ²
Thickness	ASTM D6525	7.0	mm
Light Penetration	ASTM D6567	22	% open
Water Absorption	ASTM D1117	450	%

Table 2 - Netting	
Top Net	Synthetic Photo-degradable
Bottom Net	n/a
Top Net Opening	0.50 in x 0.54 in (Nominal)
Bottom Net Opening	n/a

Table 3 - Roll Dimensions		
Style	Narrow	Wide
Roll Width	7.5 ft	15.0 ft
Roll Length	120 ft	120 ft
Coverage	100 yd ²	200 yd ²
Roll Weight	55 lbs	110 lbs